



Following:

- ENGLISH VERSION
- ITALIAN VERSION

PRY-CAM HOME TRIFASE



GENERAL INFO

Product description

The devices of the PRY-CAM Home family are part of a monitoring system for low voltage applications. The devices are designed to perform verification tests of the electrical system and to measure the electrical values at the point of electrical connection and make them available via the cloud.

This product does not constitute an active electricity meter within the meaning of the European Directive 2004/22 / EC (MID). It cannot be used as a counter for official billing. The data collected may differ from the data of the main energy meter used for the counts.

Requires a dedicated smartphone APP

This device can be used with PCH-0002 (PRY-CAM HOME PLUG).

Generic Name

PCH-005

CERTIFICATION AND DESIGN STANDARDS

Service	Article of Directive 2014/53/EU	EU Standards
RF Exposure	Article 3.1 (a): Health and Safety of the User	EN 62311:2008
Safety		EN 62368-1 + IEC 61010-1
EMC	Article 3.1 (b): Electromagnetic Compatibility	EN 301 489-1 V2.2.3: Common Part Draft EN 301 489-17 V3.2.0: WiFi @2.4 GHz Draft EN 301 489-52 V1.1.0: NB-IoT
RF	Article 3.2 : Effective use of spectrum allocated	EN 300 328 V2.2.2: Wi-Fi 802.11b/g/n 1x1 (n20, n40) EN 301 908-1 V11.1.1: NB-IoT EN 300 220-1 V3.1.1 + EN 300 220-2 V3.1.1: LoRa

APPLICATION PROPERTIES

Nominal Voltage	400 V AC [EU]
Frequency	50 - 60 Hz
Type	4P (3P + N)
Consumption	< 5 W
Max current per phase	125 A
Weight	< 500gr
Dimensions	7 DIN rail position
Storage Temperature	-10°C to +60°C
Operating Temperature	0°C to 40°C
Max Altitude	2000 m
Overvoltage category	III
Degree of protection	IP20 (inside cabinet)
Pollution Degree	2
Humidity (non-condensing)	<75% rel.
Communication Protocol	Wi-Fi, LoRa

FEATURES

Parameter under control	
4 Currents	L1, L2, L3, N
3 phase voltages	L1-N, L2-N, L3-N
3 combined tensions	L1-L2, L2-L3, L3-L1
4 phase-to-ground voltages	L1-E, L2-E, L3-E, N-E
3 active powers	P1, P2, P3
3 reactive powers	Q1, Q2, Q3
Differential current	
THD measurement	
Phases sequency	
Frequency, Cos Phi, Energy, earth loop impedance approx.	
Temperature and humidity	
Dry contact NO/NC [SPDT, 230VAC, 1A]	

OMHERO TRIFASE



INFO GENERALI

Descrizione prodotto

I dispositivi della famiglia OMHERO fanno parte di una soluzione di monitoraggio per applicazioni di bassa tensione. I dispositivi sono progettati per eseguire i test di verifica di un impianto elettrico e per rilevare i valori elettrici nei punti di misura e renderli disponibili tramite cloud.

Questo dispositivo può essere interfacciato con il dispositivo PCH-0002 (OMHERO PLUG).

Nome Generico

PCH-0005

CERTIFICAZIONI

CE RED KEMA KEUR

Service	Article of Directive 2014/53/EU	EU Standards
RF Exposure	Article 3.1 (a): Health and Safety of the User	EN 62311:2008
Safety		EN 62368-1 + IEC 61010-1
EMC	Article 3.1 (b): Electromagnetic Compatibility	EN 301 489-1 V2.2.3: Common Part Draft EN 301 489-17 V3.2.0: WiFi @2.4 GHz Draft EN 301 489-52 V1.1.0: NB-IoT
RF	Article 3.2 : Effective use of spectrum allocated	EN 300 328 V2.2.2: Wi-Fi 802.11b/g/n 1x1 (n20, n40) EN 301 908-1 V11.1.1: NB-IoT EN 300 220-1 V3.1.1 + EN 300 220-2 V3.1.1: LoRa

APPLICATION PROPERTIES

Tensione nominale	400 V AC [EU]
Frequenza	50 - 60 Hz
Tipo	4P (3P + N)
Consumo	< 5 W
Corrente nominale	125 A
Peso	< 500gr
Dimensioni	7 posizioni
Temperatura di stoccaggio	-10°C to +60°C
Temperatura operativa	0°C to 40°C
Altitudine massima	2000 m
Categoria di sovratensione	III
Grado IP	IP20 (dentro il Quadro)
Grado di inquinamento	2
Umidità relativa	<75% rel.
Protocolli di comunicazione	Wi-Fi, LoRa

FEATURES

Parametri monitorati	
4 Correnti	L1, L2, L3, N
3 Tensioni di fase	L1-N, L2-N, L3-N
3 Tensioni concatenate	L1-L2, L2-L3, L3-L1
4 Tensioni fase-terra	L1-E, L2-E, L3-E, N-E
3 Potenze attive	P1, P2, P3
3 Potenze reattive	Q1, Q2, Q3
Corrente differenziale [precisione <50 mA]	
Misura del THD	
Identificazioni sequenza delle fasi	
Frequenza, CosPhi, Energia, resistenza di terra approx	
Temperatura e umidità	
Contatti ausiliar NO/NC [SPDT, 230VAC, 1A]	